

Triphosphur Striplights

- Flicker free, long life and energy efficient
- Neat, safe, ultra slim and easy to install
- Comes complete with fixing clips, 2m input lead and 200mm link lead

Code	Description
LTR6	6 watt Triphosphur Striplight 275mm
LTR8	8 watt Triphosphur Striplight 400mm
LTR16	16 watt Triphosphur Striplight 530mm
LTR20	20 watt Triphosphur Striplight 630mm
LTR30	30 watt Triphosphur Striplight 815mm
LTRB6	Replacement 6 watt triphosphur bulb
LTRB8	Replacement 8 watt triphosphur bulb
LTRB16	Replacement 16 watt triphosphur bulb
LTRB20	Replacement 20 watt triphosphur bulb
LTRB30	Replacement 30 watt triphosphur bulb



Low Voltage Downlights & Transformers

- Low voltage downlight with 20 watt capsule bulb
- Stainless steel finish
- Recessing requires a 55mm diameter cut out (page 77)
- Stainless steel surface mounting ring also available

Code	Description
LLVSS	20 watt low voltage stainless steel downlight
LLVSSR	Stainless steel surface mounting ring
LLVT60	60 watt electronic transformer
LLVT105	105 watt electronic transformer
LLVB20C	Replacement 20 watt capsule bulb



Low Voltage Kea Lights & Transformers

- Low voltage Kea light with 20 watt capsule bulb
- Stainless steel finish

Code	Description
LLVKEA	20 watt low voltage Kea stainless steel light
LLVT60	60 watt electronic transformer
LLVT105	105 watt electronic transformer
LLVB20C	Replacement 20 watt capsule bulb



Low Voltage Stenza Overlights & Transformers

- Low voltage Stenza overlight with 20 watt bulb
- Stainless steel finish

Code	Description
LLVSTENZA	20 watt low voltage Stenza stainless steel overlight
LLVT60	60 watt electronic transformer
LLVT105	105 watt electronic transformer
LLVB20	Replacement 20 watt bulb



Low Energy LED Plinth Lights

- Set of 4no. LED plinth lights complete with 3 pin transformer
- Stainless steel finish
- 25mm diameter hole cut out required
- Connecting leads provide up to 6m of spread

Code	Description
LPL	Set of 4no. LED plinth lights stainless steel



Power Dock

- Power where you need it, when you need it
- Simply slides out when required and is stored neatly when not in use
- 2no. socket option is 268mm long and rises 185mm up from worktop
- 102mm cut out required, maximum surface thickness is 50mm
- Stainless steel finish on lid
- Other options available including computer network connections

Code	Description
APD2SS	Power Dock with 2no. sockets (20A) and 2m cable. S'steel



ISE Food Waste Disposal Unit

- .65HP continuous-feed
- 980ml capacity
- Stainless steel shredding ring with two way action
- Built in air switch
- B.E.A.B., C.E. mark and 4 year warranty
- 318mm high x 184mm diameter.

Code	Description
BWD65	.65HP ISE food waste disposal unit



in sink erator